

## ■ Hand Pallet Trucks

---

High Standards and experienced Engineering provide superior Quality!

### ▶ Basic information

---



High Standards and experienced  
Engineering provide superior Quality!

### ▶ New Valuable Features

---



#### Comfortable Molded Grip Handle

New molded handle design provides comfort and a strong grip

#### 3 Position Fingertip Control

3 position Control Lever provides easy fingertip control of complete hydraulic system

### ▶ Standard Features

---



#### Polyurethane Wheels

Rugged Polyurethane Wheels are standard

#### Lead Free Paint

Bishamon pallet trucks are painted with environmentally friendly lead free paint.

## ► Wide Range of Available Models

---



### Super Low Profile Model-40mm M/M Height

BM10-L40 Series

#### Ideal for

Vending Machine

Office machine

Thin pallet etc.



### Stainless Model

BMSH15 Series

#### Ideal for

Food Industries

Chemical Industries

Applications in the refrigerator etc.

Note:Torsion Tubes and Wheel Forks are chrome plated



### Models for Plastic Pallet

BMP11&BMP15 Series

#### Ideal for

Standard Plastic Pallet



### Models for 4 Way Pallet

BMRP Series

#### Ideal for

Especially developed for 4way plastic pallet.

Fits 1,100\*1,100 pallet without dragging when pulling truck

► Specification

Model	Model No.	Capacity (Kgs.)	Fork Dimension					Wheel Material	Weight (Kgs.)		
			A1	A2	B	D1	D2				
			mm (inch)	mm (inch)	mm (inch)	mm (inch)	mm (inch)				
A	BM20SS	2,000	520 (20 1/2")	214 (8 1/2")	810 (32")	80 (3 1/8")	200 (7 7/8")	V/V(N/N)	72		
	BM20S				980 (42")				75		
	BM20M				1,070 (48")				79		
	BM20L				1,150 (45 1/4")				81		
	BM20C				685 (27")				3779 (15")	1,070 (42")	85
	BM20LL				1,220 (48")				88		
B	BM20-46SS	2,000	460 (18 1/8")	154 (6")	810 (32")	80 (3 1/8")	200 (7 7/8")	V/V(N/N)	70		
	BM20-46S				980 (42")				74		
	BM20-60M		600 (23 5/5")	294 (11 1/2")	1,070 (42")				82		
	BM20-60L				1,150 (45 1/4")				85		
C	BM25SS	2,500	520 (20 1/2")	214 (8 1/2")	810 (32")	80 (3 1/8")	200 (7 7/8")	V/V(N/N)	83		
	BM25S				980 (42")				86		
	BM25M				1,070 (42")				89		
	BM25L				1,150 (45 1/4")				92		
	BM25C				685 (27")				379 (15")	1,070 (42")	95
	BM25				1,150 (45 1/4")				98		
	BM25LL				1,220 (48")				99		
D	BM15SS-L	1,500	520 (20 1/2")	214 (8 1/2")	810 (32")	65 (2 1/2")	165 (6 1/2")	V/S	68		
	BM15-M-L				1,070 (42")				75		

E	BM30M	3,000	520 (20 1/2")	214 (8 1/2")	1,070 (42")	80 (3 1/4")	203(8")	V/V(Bogie Wheels)	105
	BM30LL		685 (27")	379 (15")	1,220 (48")				110
F	BM15SS-L50	1,200	520 (20 1/2")	214 (8 1/2")	810 (32")	50 (2")	14 (5 1/2")	V/S	68
	BM15M-L50				1,070 (42")				75
	BM15LL-L50		685 (27")	379 (15")	1,220 (48")	83			
G	BM10SS-L40	1,000	520 (20 1/2")	214 (8 1/2")	810 (32")	40 (1 9/16")	115 (4 1/2")	V/N	64
	BM10S-L40				980 (38 1/2")				67
	BM10M-L40				1,070 (42")				71
	BM10C-L40		685 (27")	379 (15")					

H	BMSH15SS	1,500	520 (20 1/2")	214 (8 1/2")	810 (32")	80 (3 1/4")	200 (7 7/8")	N/N	72
	BMSH15M				1,070 (42")				79
	BMSH15LL		685 (27")	379 (15")	1,220 (48")	88			
	BMSH15SS-L		520 (20 1/2")	214 (8 1/2")	810 (32")	65 (2 1/2")	165 (6 1/2")		68
	BMSH15M-L				1,070 (42")				75
	BMSH15LL-L		685 (27")	379 (15")	1,220 (48")	83			